



Company Name: Ecobath Trading Ltd

Trading Name: Eco Bathroom Solutions

2C Greenmount Dr, East Tamaki, Auckland 2013

Phone: +64 9 2711456

Email: ecobath@hotmail.com

Ecobath Shower Glass BPIR Declaration

Version: 2025

Designated building product: Class 1

Declaration

Ecobath Trading Limited has provided this declaration to satisfy the provisions of Schedule 1(d) of the building (Building Product Information Requirements) Regulations 2022.

Product/System

Name: Ecobath Shower Glass

Identifier: RS04, SS, DS, FBF, F Series

Description

We offer a diverse range of shower boxes and shower cubicles.

Shower Box Configurations: 2-Sided Shower Boxes, 3-Sided Alcove Shower Boxes curved, square, rectangular, and diamond/ angle corner.

Available Sizes: 900mm x 750mm, 800mm x 800mm, 900mm x 900mm, 1000mm x 800mm, 1200mm x 900mm

Door Options: Pivot Door, Trombone Door, Bifold Door, Sliding Door

The shower glass is made of tempered glass, polished aluminum frame, seals for water tightness, chrome handle/s, certified 6mm safety glass complying with AS/NZS 2208.

All sizes are nominal, and specific availability varies according to the choose range.

Scope of Use

For interior installations in residential buildings, with timber or concrete flooring. Install as a complete Acrylic Shower Enclosure (comprising Acrylic Shower Tray, Shower Liner & Shower Door or return if applicable).

Condition of Use

Ecobath Trading Ltd Shower Glass door (& return, if applicable) must be installed and maintained in accordance with our supplied instructions.

Special attention must be paid to the specific requirement for each joint - please refer to the installation instructions for further information.

The tapware & waste must be installed by a Registered Plumber.

The maximum permitted temperature of water at the shower outlet is 50 degrees Celsius.

Relevant Building Code

B2 Durability — B2.3.1 (c)

E3 Internal moisture — E3.3.5, E3.3.6

F2 Hazardous building materials — F2.3.1, F2.3.3

G1 Personal Hygiene — G1.3.2

G13 Foul Water

Statement of Contributions to Compliance

B2 Durability:

Per B2/AS1, Durability Requirements of Nominated Building Elements for Plumbing Fixtures, Ecobath Shower Glass have a durability of at least 3 years, when installed and maintained in accordance with our supplied instructions, it is easy to access and replace, and failure would be easily detected during normal use.

E3 Internal moisture:

Surfaces of this product are likely to be splashed or become contaminated during the intended use of the building, it's impervious and easily cleaned. The minimum height for the Ecobath shower glass is 1830mm.

F2 Hazardous building materials:

This product is constructed of materials that will not emit harmful concentrations of substances from exposed surfaces. Each glass panel is manufactured & marked in accordance with AS/NZS 2208. Please contact us for the current AS/NZS 2208 certificate.

G1 Personal Hygiene:

Ecobath Shower Glass must be provided with hot water to satisfy the intended usage of personal bathing (note - tapware not included).

G13 Foul Water:

when water-borne disposal is used. This product is a sanitary fixture constructed and designed to be installed that facilitates sanitation and allows effective cleaning.

Supporting documentation

The following additional documentation supports the above statements:

Installation Instructions	Refer website.
Warranty statement(s)	Refer website.
Care & maintenance guide	Refer website.

For further information supporting Ecobath Freestanding Baths claims refer to our website.

Contact Details

Manufacture Location	China
Manufacturer	Ecobath Trading Ltd Approved Manufacture
Legal and trading name of importer	Ecobath Trading Ltd
Address for Service	2C Greenmount Drive, East Tamaki, Auckland, 2013
Importer website	https://www.ecobath.co.nz/
Importer email	ecobath@hotmail.com
Importer phone number	09 27 11 456
Importer NZBN	9429031632164