

Company Name: Ecobath Trading Ltd Trading Name: Eco Bathroom Solutions 2C Greenmount Dr, East Tamaki, Auckland 2013 Phone: +64 9 2711456 Email: ecobath@hotmail.com

Ecobath Shower Liner BPIR Declaration

Version: Nov 2025

Designated building product: Class 1

Declaration

Ecobath Trading Ltd has provided this declaration to satisfy the provisions of Schedule 1(d) of the Building (Building Product Information Requirements) Regulations 2022.

Product/system

Name: Ecobath Shower Liner

Identifier: 2-sided liner,

3 sided liner

Description

The shower liner is made from a single, folded piece of 2.0mm acrylic capped ABS sheet, it's a one piece no joints to prevent the water leakage. The recommended shower liner adhesive is Sika[®] Showerbond. Sanitary Grade Acrylic features a high gloss surface for ease of cleaning.

The surface of the shower line is white flat sheet, no molded, with transparent protective film.

2 sides sizes: 785x785, 885x885, 735x885, 985x985, 985x785, 1185x885,

3 sides sizes: 785*778*785*1900, 885*878*885*1900, 985*978*985*1900, 885*728*885*1900, 735*878*735*1900, 785*978*785*1900, 985*778*985*1900, 885*1178*885*1900

All sizes are nominal, and specific availability varies according to the choose range.

Scope of Use

For interior installations in residential buildings, with timber or concrete flooring.

Install as a complete Acrylic Shower Enclosure (comprising Acrylic Shower Tray, Shower Liner & Shower Door or return if applicable.

Hot water must be supplied to this sanitary fixture via adjacent tapware.

Condition of Use

Ecobath Shower Liner must be installed and maintained in accordance with our supplied instructions, and must be installed using only Sika[®] Showerbond adhesive. The substrate must not have been previously plastered, sealed or painted. Gaps must be left in the adhesive pattern to allow solvent release. The edge of the wall liner should not be sealed until the adhesive has been cured.

Special attention must be paid to the specific requirement for each joint.

The tapware & waste must be installed by a Registered Plumber. The maximum permitted temperature of water at the shower outlet is 50 degrees Celsius.

Relevant Building Code

- B2 Durability B2.3.1 (c)
- E3 Internal moisture E3.3.5, E3.3.6
- F2 Hazardous building materials F2.3.1, F2.3.3
- G1 Personal Hygiene G1.3.2 G12
- G13 Foul Water

Statement of Contributions to Compliance

B2 Durability	Ecobath Shower Liner have a durability of at least 3 years, when installed and maintained in accordance with our supplied instructions.
E3 Internal moisture	Surfaces of this product are likely to be splashed or become contaminated during the intended use of the building, it's impervious and easily cleaned. The liners are made from a single, folded piece of 2.0mm acrylic capped ABS sheet without any joints to prevent the water leakage. Sanitary Grade Acrylic features a high gloss surface for ease of cleaning.
F2 Hazardous building materials	This product is constructed of materials that will not emit harmful concentrations of substances from exposed surfaces.
G1 Personal Hygiene	Ecobath Shower Liner must be provided with hot water to satisfy the intended usage of personal bathing (note - tapware not included).

G13 Foul Water	when water-borne disposal is used. This product is a sanitary fixture
	constructed and designed to be installed that facilitates sanitation and
	allow effective cleaning.

Supporting Documents

The following additional documentation supports the above statements:

Installation Instructions	Refer website.
Warranty statement(s)	Refer website.
Care & maintenance guide	Refer website.

For further information supporting Ecobath Shower Liner claims refer to our website.

Contact Details

Manufacture Location Manufacturer	China Ecobath Trading Ltd Approved Manufacture
Legal and trading name of importer	Ecobath Trading Ltd
Address for Service	2C Greenmount Drive, East Tamaki, Auckland, 2013
Importer website	https://www.ecobath.co.nz/
Importer email	ecobath@hotmail.com
Importer phone number	09 27 11 456
Importer NZBN	9429031632164