



Company Name: Ecobath Trading Ltd

Trading Name: Eco Bathroom Solutions

2C Greenmount Dr, East Tamaki, Auckland 2013

Phone: +64 9 2711456

Email: ecobath@hotmail.com

Ecobath Toilets BPIR Declaration

Version: 2025

Designated building product: Class 1

Declaration

Ecobath Trading Limited has provided this declaration to satisfy the provisions of Schedule 1(d) of the Building (Building Product Information Requirements) Regulations 2022.

Product/System

Name: Ecobath Toilets

Identifier: CT1088BR, CT10180AR, CT10180ACR, Arrow2231

Description

Ecobath toilet models feature back to wall and open back models with the rimless dual flushing systems. The heavy-duty durable toilet seats are soft-closing and easy to release. Top/back inlet and left or right bottom inlet cisterns are available.

Scope of Use

Ecobath Back-to-wall & Open-back Toilets are intended for use for personal sanitation in residential & commercial buildings. All models are floor mounted & are supplied with an S trap pan connector to achieve a wide range of set outs (refer to specification sheet for each model). P trap installation is possible with a straight pan connector (not supplied).

All models feature top and bottom, left or right water inlet options.

Condition of Use

Installation must comply with AS/NZS 3500 and AS/NZS 6400. Must be installed by a registered plumber in accordance with our supplied instructions. Maximum working pressure: 500kPa. If pressure exceeds 500kPa, a pressure limiting valve must be installed. The pan must be firmly fixed to the floor using the supplied fixing kit. This product is cleanable and impervious to moisture.

Relevant Building Code

B2 Durability — B2.3.1 (c)

F2 Hazardous building materials — F2.3.1

G1 Personal Hygiene — G1.3.2

Statement of Contributions to Compliance

B2.3.1(c):

Per B2/AS1, Durability Requirements of Nominated Building Elements for Plumbing Fixtures, Ecobath Toilets have a durability of at least 3 years, when installed and maintained in accordance with our supplied instructions, is easy to access and replace, and failure would be easily detected during normal use.

F2.3.1:

No materials used in the construction of Ecobath Back-to-wall & Open-back toilets give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

G1/AS1 2.6.1:

Ecobath Toilets feature a high gloss surface for hygiene and ease of cleaning. This product is a sanitary fixture constructed and designed to be installed to discharge to a plumbing and drainage system as required by G13 "Foul Water"

Supporting documentation

The following additional documentation supports the above statements:

Installation Instructions	Refer website.
Warranty statement(s)	Refer website.
Care & maintenance guide	Refer website.

For further information supporting Ecobath Toilets claims refer to our website.

Contact Details

Manufacture Location	China
Manufacturer	Ecobath Trading Ltd Approved Manufacture
Legal and trading name of importer	Ecobath Trading Ltd
Address for Service	2C Greenmount Drive, East Tamaki, Auckland, 2013
Importer website	https://www.ecobath.co.nz/
Importer email	ecobath@hotmail.com
Importer phone number	09 27 11 456
Importer NZBN	9429031632164